

This product is a modern polyurethane resin designed as a final seal and finish to provide a tough, glossy, stain and chemical resistant finish on soft or hardwood gym floors. It can be used as a final finish or as a sealer. To use as a sealer dilute 3 parts product with 1 part mineral spirits.

DIRECTIONS FOR USE AS A SEALER:

FOR PREVIOUSLY SEALED FLOORS: If desired, apply a paint stripper or varnish remover to remove old finish. All oil, grease, soil and residue of varnish remover must be removed by dry cleaning with a waterless wood floor cleaner, and rinsed thoroughly with dry cleaning solvent. Dry overnight or until wood is dry to the touch. Buff with a #120 abrasive screen. Remove all dust by vacuum, and follow with tack rag treated with mineral spirits. Then follow directions for sealing new or sanded floors.

NEW OR SANDED FLOORS: Sweep or vacuum floor and follow with tack rag treated with mineral spirits to pick up dust. Apply this seal with a clean lamb's wool applicator. The first coat should be applied across the grain of the wood, and the second coat should be applied with the grain. A third coat, applied with the grain, may be required for extremely porous wood. Buff lightly with a #120 abrasive screen and wipe with a treated tack rag to remove all dust in preparation for the finish coat.

DIRECTIONS FOR USE AS A FINISH:

Prepare and seal the floor surface. Buff sealed floor lightly with #120 grit screen and remove all dust by vacuum and tack rag treated with mineral spirits. Apply this finish over the sealed floor using a clean lamb's wool applicator, using care to apply a smooth, even coat and allow to dry completely. If additional finish coats are desired, buff lightly with #120 grit screen and wipe with a treated tack rag between coats. Allow the finish to dry completely before any traffic is allowed onto the floor.

GYM FLOOR SEAL & FINISH

OIL MODIFIED POLYURETHANE
FOR FINISHING AND SEALING
WOOD GYM FLOORS

CONTAINS 40% SOLIDS

CAUTION

Combustible material. Harmful or fatal if swallowed. See side panel for further precautions and first aid instructions.
KEEP OUT OF REACH OF CHILDREN

Sold By:

CAUTION

Combustible material. Harmful or fatal if swallowed. Contains mineral spirits. Keep away from heat and open flame. Avoid prolonged or repeated contact with skin. Vapor is harmful. **FORCED VENTILATION IS RECOMMENDED WHEN APPLYING THIS SEAL.** If recommended exposure limits are exceeded, wear a NIOSH approved respirator, following manufacturer's recommendation. Do not use in the presence of food. In case of spill, soak up with absorbent material and place in closed container for disposal according to local environmental regulations. In case of fire, use dry chemical or CO₂ extinguisher.

FIRST AID

If Inhaled: Remove person to fresh air. If irritation or breathing difficulty persists, obtain medical attention.

If In Eyes: Flush with plenty of cool water for at least 15 minutes and obtain medical attention.

If On Skin: Wash thoroughly with soap and water.

If Swallowed: DO NOT induce vomiting. Call physician or poison control center immediately.


KEEP OUT OF REACH OF CHILDREN

Please Consult MSDS for further precautionary information.

This Product Contains	CAS Number
Petroleum Distillate	.64742-88-7
Urethane Modified Soya Alkyd Resin	.Proprietary
Mineral Spirits	.8052-41-3
Medium Oil Alkyd Resin Solution	.Proprietary
Trimethyl Benzene	.25551-13-7

NFPA® RATINGS

Flammability



0128.033105

NET CONTENTS:

5 6 20 30 55

GALLONS