

Dissolves rust, lime, minerals and scale on hard surfaces such as machinery parts, water meters and cement trucks. Cleans radiators, boilers, cooling systems and metal surfaces. Restores the natural color to brick or stone that is discolored from wear or weathering. Dissolves carbonates for quick removal of mortar, plaster, cement and concrete.

DIRECTIONS

To clean and descale water meters and metal parts, submerge parts in undiluted cleaner and soak until all deposits are dissolved. Rinse thoroughly with clean water. For light deposits, dilute with 3 to 5 parts water.

To remove excess mortar, plaster, cement and concrete forms walls, siding, transit forms and mixing machinery, use full strength. Always rinse thoroughly after use.

To clean and descale boilers, cooling towers, condensers, heat exchangers and other water handling systems, dilute with 8 to 10 parts water. Allow diluted solution to soak or circulate in system for 4 to 8 hours or until scale is removed. Flush system thoroughly with clean water.

Rinse empty container before disposal. Use plastic containers to mix solutions – do not store in metal pails, drums or sprayers.

MURIATIC ACID CLEANER

DISSOLVES DEPOSITS OF
RUST, LIME, MINERAL SCALE

SPECIAL INHIBITORS
PROTECT METAL SURFACES

DANGER  **POISON**

MAY BE FATAL IF SWALLOWED.

CAUSES SEVERE BURNS. VAPOR HARMFUL.

See side panel for further cautions
and first aid instructions.

KEEP OUT OF REACH OF CHILDREN

Sold By:

DANGER  **POISON**

MAY BE FATAL IF SWALLOWED.

CAUSES SEVERE BURNS. VAPOR HARMFUL.

Contains hydrochloric acid. Do not inhale or swallow. Keep away from skin, eyes and clothing. Wear rubber gloves and eye protection when handling. Use with adequate ventilation. Do not mix with any other chemical.

FIRST AID:

IF IN EYES: Flush eyes and under eyelids with water for at least 15 minutes. Obtain medical attention.

IF ON SKIN: Wash with soap and water. Remove contaminated clothing and laundry before reuse. If irritation is persistent, contact a physician.

IF SWALLOWED: Contact physician or poison control center immediately. Do not induce vomiting. Drink large quantities of water, followed with milk of magnesia, beaten eggs or vegetable oil

IF INHALED: Remove person to fresh air. Obtain medical attention.


See M.S.D.S. for complete safety information.

KEEP OUT OF REACH OF CHILDREN

Handling & Storage: Keep container tightly closed when not in use. Do not store in unmarked containers. Use plastic containers to mix solutions – do not store in metal pails, drums or sprayers. Keep away from alkaline materials, metals and metal salts. Rinse empty container before disposal.

This product contains:	CAS Number
Hydrochloric Acid7647-01-0
Water7732-18-5
Poly (oxyethylene) nonylphenol9016-45-9
Ethoxylated Amine Resin61790-47-4
Green Dye61791-17-1

NFPA® RATINGS
Flammability



0140.091004

NET CONTENTS:

5 6 20 30 55

GALLONS