

This vapor-suppression product is designed for use by fire departments, port authorities, sewer treatment plants, industry and municipalities to reduce the fire hazard associated with flammable liquid spills. This surface active agent emulsifies fuels and hydrocarbons with water. Fire hazard is significantly reduced by the resulting suppression of any flammable or combustible vapors. This formula contains no alcohol, solvents or petroleum distillates.

DIRECTIONS

This vapor suppression chemical must be applied to the spill with sufficient agitation to break up the slick. Agitation may be by mechanical means or by the action of the hose stream.

To emulsify small spills, apply directly to the spill area with a hand sprayer, then flush thoroughly with water.

For large spills on water, inject this vapor suppression chemical into hose stream with standard eductor equipment. Do not use with a foam nozzle.

WARNING: This product will not disperse vapors accumulated in any closed areas. Take all precautions necessary to prevent hazard from vapor accumulations.

NOTE: This product will not make spills non-hazardous. Do not flush to drains leading to sanitary or storm sewers. Please consult local environmental authorities for proper disposal.

Spills of fuel or other hazardous materials must be reported to the proper authorities, as prescribed by applicable state and Federal laws and regulations.

NO MORE VAPOR

EMULSIFIES AND DISPERSES
FUELS, SOLVENTS AND OILS

ELIMINATES FLAMMABLE
OR EXPLOSIVE VAPORS

CAUTION

May irritate eyes. Avoid contact with eyes.
See side panel for further cautions and first aid instructions.

KEEP OUT OF REACH OF CHILDREN

Sold By:

CAUTION

May irritate eyes. Avoid contact with eyes. Avoid prolonged or repeated contact to skin.

FIRST AID

IF IN EYES: Flush eyes and under eyelids with cool water for at least 15 minutes. If irritation persists, obtain medical attention.

IF ON SKIN: Wash with water. If irritation persists, obtain medical attention.

IF SWALLOWED: Drink several glasses of water. Do not induce vomiting. Call a physician immediately.

KEEP OUT OF REACH OF CHILDREN

Please consult MSDS for further precautionary information.

This product contains	CAS Number
Poly(oxyethylene)nonylphenol	9016-45-9
Octylphenoxy polyethoxyethanol	9036-19-5
Sodium Xylene Sulfonate	1300-72-7
Water	7732-18-5

0158.032103

NET CONTENTS:

5 6 20 30 55

GALLONS

NFPA RATINGS
Flammability

