

FUEL AID PLUS

This premium additive helps all types of engines run clean and more efficiently. Special detergents remove deposits and clogs from fuel injection systems for better acceleration, no stall, stumble, or run-on. Dispersant and corrosion inhibitor additives clean gums, varnish, and corrosion deposits from fuel tank, delivery system and carburetors – and protects from further corrosion. It extends engine life by eliminating intake valve deposits, and lubricating upper cylinders under cold start conditioners.

This formula improves the performance of all vehicles, including those with catalytic converters and modern computer-controlled engines.

DIRECTIONS:

Use 12 ounces for every 20 gallons of gasoline.

In bulk storage tanks, use 2 to 3 gallons per 1000 gallons of gasoline.

MULTI-FUNCTIONAL
GASOLINE ADDITIVE

REDUCES INTAKE VALVE,
CARBURETOR, AND
PORT FUEL INJECTOR DEPOSITS

REDUCES EMISSIONS
RUST & CORROSION PROTECTION
FOR FUEL SYSTEM

GOOD WATER REMOVAL

CAUTION – COMBUSTIBLE
HARMFUL OR FATAL IF SWALLOWED.
KEEP AWAY FROM HEAT OR OPEN FLAME.
See side panel for additional precautions.
KEEP OUT OF REACH OF CHILDREN

Sold By:

CAUTION – COMBUSTIBLE

Harmful or fatal if swallowed.
Keep away from heat, spark, or open flame.

FIRST AID:

IF SWALLOWED: Contact a physician or poison control center immediately. DO NOT induce vomiting.

IF IN EYES: Flush eyes with water for at least 15 minutes. If irritation is persistent, contact a physician.

IF ON SKIN: Wash skin with soap and water. Remove all contaminated clothing and launder separately before reuse. If irritation is persistent, contact a physician.

IF INHALED: Remove person to fresh air. If irritation is persistent, contact a physician.

See M.S.D.S. for complete safety information.

KEEP OUT OF REACH OF CHILDREN

HANDLING & STORAGE: Keep container tightly closed when not in use. Avoid excess heat and open flame. Do not store in unmarked containers. Rinse empty container before disposal.

This product contains	CAS Number
Light Aromatic Solvent Naphtha	.64742-95-6
Hydrocarbylamine	.Proprietary
Hydrocarbon solvent	.Proprietary
Petroleum naphtha	.64742-94-5
Polyetheramine	.Proprietary



0649.091205

NET CONTENTS:

5 6 20 30 35 55
GALLONS