

This concentrated alkaline cleaner rapidly penetrates, loosens and removes encrusted soil deposits, grease and oils. Dissolves quickly and rinses freely. For use on ferrous and most non-ferrous metals found in auto service shops on engine blocks and radiators, in boilers and heat exchangers, in food processing establishments, machine shops and industrial use.

**DIRECTIONS:**

For normal cleaning, dissolve 16 ounces in 3 gallons of water. For extremely soiled surfaces, or heavy deposits a stronger solution may be required. For best results, the temperature of the hot tank should be maintained between 180°F and 190°F.

# STEAM & HOT TANK CLEANER

DISSOLVES QUICKLY AND COMPLETELY

**DANGER**  **POISON**

CAUSES SEVERE BURNS.  
HARMFUL OR FATAL IF SWALLOWED.  
See side panel for additional precautions.  
**KEEP OUT OF REACH OF CHILDREN**

Sold By:

**DANGER**  **POISON**

CAUSES SEVERE BURNS.

Harmful or fatal if swallowed. May cause severe eye and skin irritation. Prolonged or repeated exposure may cause skin irritation. Use with adequate ventilation.

**FIRST AID:**

**If Swallowed:** Call a physician immediately. Do not induce vomiting. Give affected person 1-2 glasses of water. Never give anything to an unconscious person.

**If On Skin:** Wash with soap and water. Remove contaminated clothing and laundry before reuse. If irritation is persistent, contact a physician.

**If In Eyes:** Flush eyes and under eyelids with cool water for at least 15 minutes and obtain medical attention.

**If Inhaled:** Remove person to fresh air. Call a physician immediately.

**KEEP OUT OF REACH OF CHILDREN**

See M.S.D.S. for complete safety information

**Handling & Storage:** Keep container tightly closed when not in use. Do not store in unmarked containers. Store container in cool, dry place. Do not cut or weld on or near this container even when empty. Store away from heat or open flame.

THIS PRODUCT CONTAINS	CAS NUMBER
Sodium Carbonate .....	497-19-8
Sodium Metasilicate .....	6834-92-0
Sodium Tripolyphosphate .....	7758-29-4
Sodium Hydroxide .....	1310-73-2
Poly (Oxyethylene) Nonylphenol .....	9016-45-9

0662.041204

NET CONTENTS:



25 Lbs.



50 Lbs.



100 Lbs.

**NFPA RATINGS**  
Flammability

