

# MATERIAL SAFETY DATA SHEET

Total Solutions  
P.O. Box 240014  
Milwaukee, WI 53224



GENERAL INFORMATION NUMBER: (414) 354-6417  
CHEMTREC: (800) 424-9300

REVISION DATE: July 23, 2004  
DATE OF ISSUE: August 9, 2004

## I - Product Identification

### Hydro Power Carpet Spot & Stain Remover

PRODUCT CODE: 0716

CHEMICAL FORMULATION: Oxygenated cleaner.

NFPA HAZARD IDENTIFICATION SYSTEM: HEALTH: 1 FLAMMABILITY: 0 REACTIVITY: 0  
HAZARD RATING: 4 - Extreme; 3 - High; 2 - Moderate; 1 - Slight; 0 - Insignificant

## II - Hazardous Ingredients

Values reported as TWA unless noted.

SUBSTANCE	APPROX	OSHA	ACGIH	EPA 40 CFR:			CAS#
	%	PEL	TLV	302	355	372	
Hydrogen Peroxide	1.00-5.00	1 ppm	1 ppm	N	N	N	7722-84-1

Key: PEL: Permissible Exposure Limit TLV: Threshold Limit Value C: Ceiling level STEL: Short Term Exposure Limit  
N/A: Not Applicable N/D: Not Determined N/E: Not Established Y: Yes N: No  
302: CERCLA List of Hazardous Substances and Reportable Quantities (40 CFR 302.4).  
355: SARA TITLE III / List of Extremely Hazardous Substances for Emergency Planning and Notification (40 CFR 355).  
372: SARA TITLE III / List of Toxic Chemicals subject to Release Reporting (Community Right to Know) (40 CFR 372).

## III - Physical Data

BOILING POINT (°F): N/D SPECIFIC GRAVITY (WATER = 1): 1.01  
VAPOR PRESSURE (mm Hg): N/D VOC CONTENT (% by weight): < 1.00  
VAPOR DENSITY (AIR = 1): N/D EVAPORATION RATE (WATER = 1): N/D  
SOLUBILITY IN WATER: Soluble pH: 9.0-10.0  
APPEARANCE AND ODOR: Clear, colorless liquid; citrus fragrance.

## IV - Fire and Explosion Hazard Data

FLASH POINT (°F): None (TEST METHOD): Closed cup  
FLAMMABLE LIMITS IN AIR (VOLUME %) UPPER: N/A LOWER: N/A  
EXTINGUISHING MEDIA: Water.  
SPECIAL FIRE FIGHTING PROCEDURES: Cool fire exposed containers with water fog. Firefighters should be equipped with full protective gear including self-contained breathing apparatus.  
UNUSUAL FIRE AND EXPLOSION HAZARD: This product contains an oxidizer. Mixtures with combustible or flammable materials may ignite easily, burn fiercely, or may explode in contaminated, closed containers.

---

**V - Reactivity Data**

---

**STABILITY:** Stable

**INCOMPATIBILITY:** Highly alkaline products, metals, salts, organics, reducing agents.

**CONDITIONS TO AVOID:** Excess heat (>100 F).

**HAZARDOUS DECOMPOSITION PRODUCTS:** Thermal decomposition may produce oxides of carbon, heat, steam, oxygen gas.

**HAZARDOUS POLYMERIZATION:** Will not occur.

**CONDITIONS TO AVOID:** None

---

**VI - Health Hazard Data**

---

**ROUTES OF ENTRY**      **INHALATION:** X      **EYE CONTACT:** X      **SKIN CONTACT:** X      **INGESTION:** X

**INGREDIENTS THAT ARE CONSIDERED BY OSHA, NTP, IARC TO BE SUSPECTED HUMAN CARCINOGENS:** None

**EFFECTS OF OVEREXPOSURE**

**IF IN EYES:** Mild to moderate irritation, redness tearing. Prolonged contact may cause injury.

**IF ON SKIN:** May cause irritation, with prolonged or repeated exposure.

**IF SWALLOWED:** Small amounts may cause nausea, cramps. Larger amounts may be harmful.

**IF INHALED:** May cause irritation to upper respiratory tract.

**EMERGENCY AND FIRST AID PROCEDURES**

**IF IN EYES:** Flush eyes and under eyelids with plenty of cool water for at least 15 minutes. If irritation persists, obtain medical attention.

**IF ON SKIN:** Flush skin with water. Remove contaminated clothing and rinse with water. Launder clothing separately before reuse.

**IF SWALLOWED:** Contact physician or poison control center immediately. Do not induce vomiting. Rinse mouth with water and give one to two glasses to dilute. Never give anything by mouth to an unconscious person.

**IF INHALED:** Remove person to fresh air. Administer artificial respiration if breathing has stopped.

---

**VII - Spill or Leak Protection**

---

**STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:** Ventilate area and remove all sources of ignition. Contain spill.

Soak up spilled material with inert absorbent material and place in a properly marked closed container for proper disposal.

**WASTE DISPOSAL METHOD:** Consult local environmental authorities.

---

**VIII - Special Protection Information**

---

**RESPIRATORY PROTECTION:** Use with adequate ventilation. If recommended Exposure Limits are exceeded wear a NIOSH approved respirator, following manufacturer's recommendations.

**VENTILATION**

**LOCAL:** Recommended

**MECHANICAL:** Not required

**PROTECTIVE GLOVES:** Chemical resistant.

**EYE PROTECTION:** Safety glasses.

**OTHER PROTECTIVE EQUIPMENT:** Protective clothing.

**PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:** Store in a cool, dry place away from heat, sparks or open flame.

Keep container tightly closed when not in use.

**OTHER PRECAUTIONS:** Keep out of reach of children.

---

**IX - Transportation Information (ground transportation only)**

---

**DOT PROPER SHIPPING NAME:** None

**DOT CLASS:** None

**DOT ID NUMBER:** None

**DOT PACKING GROUP:** None

The shipping information listed above applies only to non-bulk (< 119 gallons) containers of this product. This product may have more than one proper shipping name depending on packaging, product properties, & mode of shipment. If any alteration of packaging, product, or mode of transportation is further intended, different shipping names and labeling may apply.

---

**REVISION DATE:** July 23, 2004

**Prepared by:** PMR

**DATE OF ISSUE:** August 9, 2004

This information contained herein is based on data considered accurate. However, no warranty is expressed or implied regarding the accuracy of this data or the results to be obtained from the use thereof. Total Solutions assumes no responsibility for personal injury or property damage to the vendee, users or third parties caused by the material such vendees or users assume all risks associated with the use of this material.