

★ **GOLDSTAR** ★
PRODUCTS, INC.

SWITCH IT

EXTREME TEMPERATURE &
EXTREME PRESSURE LUBRICANT

NON-MELTING

NON-HARDENING

CAUTION - COMBUSTIBLE

May be harmful or fatal if swallowed.
Keep out of reach of children
See side panel for additional precautions.
KEEP OUT OF REACH OF CHILDREN

REORDER FROM:

GOLDSTAR PRODUCTS, INC.

P.O. Box 291630

Davie, FL 33329

1-800-239-5699

Provides long-term protection even when exposed to steam, damp atmospheres and salt spray. Protects metal parts under sustained temperatures up to 2100°F (1050°C). Anti-seize acts as a sealant, reduces friction, makes tighter, firmer joints that open easier reducing torque requirements.

USEFUL ON THESE SURFACES:

Cast Iron
Steel alloys
Aluminum
Copper
Brass
Titanium
Rubber-Natural and Synthetic

DIRECTIONS FOR USE:

Clean surface of oil, grease and dirt. Use with grease or gun pressure pump. Keep container tightly closed when not in use.

Note: May harm painted or waxed surfaces. Always test inconspicuous areas before using.

CAUTION - COMBUSTIBLE

May be harmful or fatal if swallowed. May irritate eyes and skin. Prolonged or repeated exposure may cause irritation. Use with adequate ventilation.

FIRST AID

If Swallowed: Do not induce vomiting. Call a physician immediately.

If Inhaled: Remove person to fresh air. If irritation persists, obtain medical attention.

If In Eyes: Flush eyes and under eyelids with cool water for at least 15 minutes. If discomfort persists see a physician.

If On Skin: Wash with soap and water. Remove contaminated clothing, and launder before reuse. If irritation is persistent, contact a physician.

KEEP OUT OF REACH OF CHILDREN

See M.S.D.S. for complete safety information

Handling & Storage: Keep container tightly closed when not in use. Do not store in unmarked containers. Store container in cool, dry place. Do not cut or weld on or near this container even when empty. Store away from heat or open flame.

This product contains	CAS Number
Aliphatic Petroleum Distillates8052-41-3
Petroleum Oil64742-52-5
Graphite7782-42-5

NFPA RATINGS

Flammability



0336.112403

NET CONTENTS: 5 GALLONS