

★ **GOLDSTAR** ★
PRODUCTS, INC.

RUST OFF

HALTS EXISTING RUST AND PREVENTS
FUTURE CORROSION WITH A DURABLE
PROTECTIVE BARRIER

NO NEED FOR SAND BLASTING,
GRINDING OR SCRAPING

CAUTION

May be harmful or fatal if swallowed.
Eye irritant. See side panel for further
cautions and first aid instructions.
KEEP OUT OF REACH OF CHILDREN

REORDER FROM:
GOLDSTAR PRODUCTS, INC.
P. O. Box 291630
Davie, FL 33329
1-800-239-5699

This new surface conditioner and primer changes rust into a dark protective polymeric coating. It converts existing rust to an inert coating that seals out moisture to prevent future rust and corrosion. This rust converter provides an excellent primer coating for the application of quality oil-based paints. Surfaces protected with this primer and an oil-based paint system resists the effects of weather, rain, sun and salt spray without peeling or cracking. This easy-to-use product is the first step in providing long-term protection of steel and iron surfaces.

DIRECTIONS FOR USE

SURFACE PREPARATION: Remove large rust and scale particles with a wire brush or sandpaper. Clean the surface thoroughly to remove dirt, dust and grease.

APPLICATION: SHAKE OR STIR WELL BEFORE USING! Apply this product using a brush or roller. This product is ready-to-use – NO thinning is required.

COVERAGE: 500 square feet per gallon on a smooth, non-porous surface. Irregular, porous or textured surfaces may require more product.

DRYING TIME: The resulting coat will dry to a smooth, dark finish in 20 minutes. Apply a second coat to ensure complete transformation of rusty surfaces. Allow 48 hours of cure time before the application of the finished paint coat.

For long-lasting protection of iron surfaces, the cured rust converter coating should be sealed with two coats of a high quality oil-based paint. No other primer is required.

CLEAN-UP: Application equipment should be cleaned immediately with soap and water.

GENERAL: Do not apply this product if the surface temperatures are below 50°F. Store in a cool, dry place, protected from freezing or temperatures above 100°F.

**IMPORTANT: DO NOT RETURN UNUSED
MATERIAL TO ORIGINAL CONTAINERS**

CAUTION

May be harmful or fatal if swallowed. Avoid contact with eyes and mucous membranes. Avoid prolonged or repeated contact with skin. Use with adequate ventilation.

FIRST AID

IF SWALLOWED: Contact physician or poison center immediately. Rinse mouth with water and give person 1 to 2 glasses of water. Never give anything by mouth to an unconscious person.

IF IN EYES: Flush eyes with water for at least 15 minutes. If irritation is persistent, contact a physician.

IF ON SKIN: Wash skin with soap and water. Remove all contaminated clothing and launder separately before reuse. If irritation is persistent, contact a physician.

IF INHALED: Remove person to fresh air.

KEEP OUT OF REACH OF CHILDREN

*See M.S.D.S. for complete safety
information.*

This product contains:	CAS Number:
Proprietary Polymer.....	No CAS Number
Water.....	7732-18-5
Tannic acid.....	1401-55-4
2-Butoxyethanol.....	111-76-2
Hydrous Silica Salt.....	53320-86-8

0346.060707

NFPA® RATINGS
Flammability



NET CONTENTS: 5 GALLONS