

★ **GOLDSTAR** ★  
PRODUCTS, INC.  
**TANK GUARD**  
**2000**

PROTECT WATER STORAGE SYSTEMS  
FROM RUST AND CORROSION

COLORLESS – ODORLESS

CONTAINS NO CHROMATES  
OR HEAVY METALS

**CAUTION**

Irritant. Avoid contact with eyes or prolonged contact with skin. See side panel for further cautions and first aid instructions.

**KEEP OUT OF REACH OF CHILDREN**

REORDER FROM:  
**GOLDSTAR PRODUCTS, INC.**  
P.O. Box 291630  
Davie, FL 33329  
**1-800-239-5699**

This product inhibits rust and corrosion formation in all metal water tanks. Designed for fire departments, utility, industrial and municipal storage tanks, laundry and hotel water storage systems and emergency water supply facilities. It forms a thin protective film on exposed metal surfaces. This non-toxic, odorless and tasteless inhibitor protects all metals including iron, steel, galvanized, brass, bronze, copper and alloys. It leaves no toxic residue, so treated tanks may be used for potable water without cleaning or rinsing.

**DIRECTIONS**

In fire truck tanks, emergency storage tanks, back pack sprayers and holding tanks, add 1 gallon of product for each 1000 gallons of water. Treat every time the tank is filled.

In flowing systems, inject or meter 3 gallons per 10,000 gallons of water. After a 6 to 8 week initial treatment period, decrease the feed rate to 1 gallon per 10,000 gallons of water.

**CAUTION**

Irritant. Avoid contact with eyes or prolonged contact with skin. Concentrate may be harmful if swallowed.

**FIRST AID**

**External:** Flush with plenty of cool water.

**Internal:** Do not induce vomiting. Give person several glasses of water and obtain immediate medical attention.

**Eyes:** Flush eye and under eyelids with plenty of cool water for at least 15 minutes and obtain medical attention.

**KEEP OUT OF REACH OF CHILDREN**

This product contains	CAS Number
Water .....	7732-18-6
Sodium Silicate .....	1344-09-8

62791300

**NET CONTENTS: 5 GALLONS**