

★ **GOLDSTAR** ★
PRODUCTS, INC.

NO-STICK

REPLACES DIESEL
ECONOMICAL
CLEAN AND SAFE
VERSATILE

CAUTION

May irritate eyes and skin.
See side panel for additional precautions.
KEEP OUT OF REACH OF CHILDREN

NET CONTENTS: 6 GALLONS

REORDER FROM:
GOLDSTAR PRODUCTS, INC.
P.O. Box 291630
Davie, FL 33329
1-800-239-5699

DESCRIPTION:

This product is an asphalt release that encapsulates dump beds, rollers, tools and equipment with a molecular film that prevents sticking and adhesion of asphalt.

USES:

Developed as an effective alternative to diesel fuel, now banned for this use by the E.P.A. Provides a thin uniform emulsion that acts like millions of ball bearings between equipment surface and the hot sticky asphalt. May be sprayed to form a heat-resistant shield that will not run off, reducing the chance of soil contamination.

SNOW:

The product's molecular film also encapsulates snow plows and dump beds to prevent snow from sticking and causing expensive down time.

APPLICATION 1:

May be applied manually by mixing one quart of product with 2 to 2-1/2 gallons of water and applying with a 3 gallon sprayer. Must agitate briskly to ensure good mixture.

APPLICATION 2:

For large volume usage, use with a proportioning device diluting one part release agent with 20 parts of water.

CAUTION:

May irritate eyes and skin.

FIRST AID:

If Swallowed: Contact a physician or poison control center immediately. Give person 1 - 2 glasses of water. DO NOT induce vomiting.

If In Eyes: Flush eyes with water for at least 15 minutes. If irritation is persistent, contact a physician.

If On Skin: Wash with soap and water. If irritation is persistent, contact a physician.

See MSDS for complete safety information.

KEEP OUT OF REACH OF CHILDREN

Handling & Storage: Keep container tightly closed when not in use. Avoid strong acids. Do not store in unmarked containers. Rinse empty container before disposal.

THIS PRODUCT CONTAINS	CAS NUMBER
Water	7732-18-5
Blended Tall Oil Distillates	8002-26-4
Tetrasodium EDTA	64-02-8
Potassium Hydroxide	1310-58-3
Methyl Ester of Soybean Oil	67784-80-9

0700.063006

NFPA® RATINGS
Flammability

