

This special wetting agent is designed to help fight stubborn, smoldering fires in upholstery, bedding, paper, hay and brush. Treated water penetrates more quickly, extinguishing the blaze with only 1/3 as much water.

This formula is biodegradable and non-corrosive. It will not harm water tanks or fittings and is compatible with all fire fighting foams and tank protectors.

#### DIRECTIONS

For increasing the wetting ability of water used in fire fighting, use 1/2 to 1 gallon per 100 gallons of water.

This wetting agent also helps to control dust on unpaved roads and yards. Mix 1 to 2 quarts per 100 gallons of water for spraying over road surfaces.

To hold down the dust from mechanical sweepers, add 1 to 2 quarts per 100 gallons of wash water.

# WATER WETTER

CHEMICAL ADDITIVE  
INCREASES THE WETTING  
AND PENETRATING  
ABILITY OF WATER

#### CAUTION

May irritate eyes.

See side panel for additional precautions.

**KEEP OUT OF REACH OF CHILDREN**

Sold By:

#### CAUTION

May irritate eyes.

#### FIRST AID

**If In Eyes:** Flush eyes and under eyelids with water for at least 15 minutes. If discomfort persists see a physician.

**If Swallowed:** Give several glasses of water and induce vomiting. Call a physician immediately.

**If On Skin:** Wash with soap and water. Remove contaminated clothing and launder before reuse. If irritation is persistent, contact a physician.

**If Inhaled:** Remove person to fresh air. Call a physician in irritation persists.

See M.S.D.S. for complete safety information.

**KEEP OUT OF REACH OF CHILDREN**

Handling & Storage: Keep container tightly closed when not in use. Do not store in unmarked containers. Store container in a cool, dry place.

This Product Contains	CAS Number
Water	7732-18-5
Alkyl Phenol Ethoxylate	9016-45-9

0395.021204

NFPA RATINGS	
FLAMMABILITY	0
HEALTH	0
REACTIVITY	0

NET CONTENTS:

5 6 20 30 55

GALLONS